

View Online at https://aerobasegroup.com/nsn/5910-01-146-9626

Body Style: Dual inline Reliability Indicator: Not established Body Length: Between 0.787 inches and 0.795 inches Body Width: Between 0.240 inches and 0.260 inches Capacitance Value Per Section: 330.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: - - Demilitarization: No Fig: A010b0	
Reliability Indicator: Not established Body Length: Between 0.787 inches and 0.795 inches Body Width: Between 0.240 inches and 0.260 inches Capacitance Value Per Section: 330.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Caramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Sheff Life: N/a Unit of Measure: - Demilitarization: No Filig:	Body Style:
Not establishedBody Length:Between 0.787 inches and 0.795 inchesBody Width:Between 0.240 inches and 0.260 inchesCapacitance Value Per Section:330.000 picofarads single sectionVottage Tempurature Limits Per Section In Percent Capacitance Change:15.0/+15.0 without voltage applied single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 125.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:50.0 dc single sectionTolerance Range Per Section:-10.00/+10.00 percent single sectionCase Material:2.5000Terminal Type And Quantity:16 pinShelf Life:N'aUnit of Measure:Demilitarization:NoFilig:	Dual inline
Body Length:Between 0.787 inches and 0.795 inchesBody Width:Between 0.240 inches and 0.260 inchesCapacitance Value Per Section:330.000 picofarads single sectionVoltage Tempurature Limits Per Section In Percent Capacitance Change:-15.0/+15.0 without voltage applied single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 125.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:50.0 dc single sectionFolerance Range Per Section:-10.00/+10.00 percent single sectionCaramicDissipation Factor At Reference Tempurature In Percent:2.5000Ferminal Type And Quantity:16 pinShelf Life:N/aUnit Of Measure:Penilitarization:NoFig:	Reliability Indicator:
Between 0.787 inches and 0.795 inches Body Width: Between 0.240 inches and 0.260 inches Capacitance Value Per Section: 330.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: 15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section 10.00/+10.00 percent single section Caramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: N/a Via Dist of Measure: Panilitarization: No Fig:	Not established
Body Width: Between 0.240 inches and 0.260 inches Capacitance Value Per Section: 330.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
Between 0.240 inches and 0.260 inches Capacitance Value Per Section: 330.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between 0.787 inches and 0.795 inches
Capacitance Value Per Section: 330.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Body Width:
 330.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: 15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fiig: 	Between 0.240 inches and 0.260 inches
Voltage Tempurature Limits Per Section In Percent Capacitance Change:-15.0/+15.0 without voltage applied single sectionNonderated Operating Temp:Between -55.0 degrees celsius and 125.0 degrees celsiusNonderated Continuous Voltage Rating And Type Per Section:50.0 dc single sectionTolerance Range Per Section:-10.00/+10.00 percent single sectionCase Material:CeramicDissipation Factor At Reference Tempurature In Percent:2.5000Terminal Type And Quantity:16 pinShelf Life:N/aUnit Of Measure:Permilitarization:NoFiig:	Capacitance Value Per Section:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No	330.000 picofarads single section
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No	Voltage Tempurature Limits Per Section In Percent Capacitance Change:
Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No	-15.0/+15.0 without voltage applied single section
Nonderated Continuous Voltage Rating And Type Per Section:50.0 dc single sectionTolerance Range Per Section:-10.00/+10.00 percent single sectionCase Material:CeramicDissipation Factor At Reference Tempurature In Percent:2.5000Terminal Type And Quantity:16 pinShelf Life:N/aUnit Of Measure:NoFig:	Nonderated Operating Temp:
50.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No	Between -55.0 degrees celsius and 125.0 degrees celsius
Tolerance Range Per Section:-10.00/+10.00 percent single sectionCase Material:CeramicDissipation Factor At Reference Tempurature In Percent:2.5000Terminal Type And Quantity:16 pinShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Nonderated Continuous Voltage Rating And Type Per Section:
 -10.00/+10.00 percent single section Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: 	50.0 dc single section
Case Material: Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin 5helf Life: N/a Unit Of Measure: Demilitarization: No	Tolerance Range Per Section:
Ceramic Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-10.00/+10.00 percent single section
Dissipation Factor At Reference Tempurature In Percent: 2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No	Case Material:
2.5000 Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ceramic
Terminal Type And Quantity: 16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Dissipation Factor At Reference Tempurature In Percent:
16 pin Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2.5000
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	16 pin
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A010b0	Fiig:
	A010b0