

View Online at https://aerobasegroup.com/nsn/5910-01-146-9628

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.0000

#### **Terminal Length:**

1.625 inches

#### **Body Diameter:**

0.400 inches

**Body Length:** 

0.938 inches

**Terminal Diameter:** 

0.032 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

# **Capacitance Value Per Section:**

1.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

#### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

250000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

0.2500

# **Case Insulation Material:**

Plastic

# Test Data Document:

81349-mil-c-39022/10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

## Shelf Life:

N/a

Unit Of Measure:



Demilitarization:

No

Fiig:

A010b0