

View Online at <https://aerobasegroup.com/nsn/5910-01-148-4857>

**Body Style:**

W/o mtg facilities terminal (s) on one surface/w/o mtg facilities terminal(s) on one surface/w/o mtg facilities terminal(s) on one surface

**Reliability Indicator:**

Not established/not established/not established

**Terminal Length:**

Between 1.500 inches and 1.500 inches and 1.500 inches and 1.750 inches 1.750 inches 1.750 inches

**Body Length:**

0.120 inches

**Body Width:**

0.165 inches

**Body Height:**

0.070 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.080 inches and 0.120 inches

**Terminal Diameter:**

Between 0.009 inches and 0.011 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**End Application:**

Sru-b apx-101 e/i fscm 45413

**Capacitance Value Per Section:**

0.470 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

35.0 dc single section

**Tolerance Range Per Section:**

-5.00/+5.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.0000

**Dc Leakage At Reference Temp:**

0.500 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0