NSN 5910-01-148-6025

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-148-6025

| Body Style: |
|--|
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.000 inches |
| Body Length: |
| 0.930 inches |
| Body Width: |
| 0.240 inches |
| Body Height: |
| 0.430 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.800 inches |
| Terminal Diameter: |
| 0.032 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| End Application: |
| Communications system type an/grc-212 |
| Capacitance Value Per Section: |
| 100000.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 400.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 250.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -200.0/+200.0 single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 30000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 1.0000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |

2 uninsulated wire lead

NSN 5910-01-148-6025

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A010b0