## NSN 5910-01-149-1036

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-149-1036

Body Style:			
W/o mtg facilities, terminal (s) on one endw/o mtg facilities	, terminal(s) on one endw/o mtg facilities,	terminal(s)	on one end
Reliability Indicator:			

Not establishednot established

**Terminal Length:** 

1.000 inches 1.000 inches 1.000 inches

**Body Diameter:** 

0.512 inches

**Body Length:** 

1.024 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.200 inches

**Terminal Diameter:** 

0.025 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

2.0

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

220.000 microfarads single section

**Nonderated Operating Temp:** 

Between -25.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

35.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+50.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

Dc Leakage At Reference Temp:

231.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-149-1036

Electrolytic Fixed Capacitor - Page 2 of 2



She	lf I	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0