NSN 5910-01-149-4245

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-149-4245

Body Style:							
W/o mtg facilities, terminals on opposite surfaces							
Mil-std-1276 Wire Lead Type Designator:							
N-c							
Reliability Indicator:							
Not established							
Terminal Length:							
1.500 inches							
Body Length:							
3.410 inches							
Body Width:							
Between 0.755 inches and 0.775 inches							
Body Height:							
Between 0.760 inches and 0.810 inches							
Terminal Diameter:							
Between 0.038 inches and 0.042 inches							
Schematic Diagram Designator:							
No common or grounded electrode (s)							
Features Provided:							
Burn in and hermetically sealed case							
Insulation Resistance At Maximum Operating Temp:							
400.0 megohm-microfarads							
Capacitance Value Per Section:							
10.000 microfarads single section							
Nonderated Operating Temp:							
Between -55.0 degrees celsius and 100.0 degrees celsius							
Nonderated Continuous Voltage Rating And Type Per Section:							
300.0 dc single section							
Tolerance Range Per Section:							
-10.00/+10.00 percent single section							
Case Material:							
Metal							
Insulation Resistance At Reference Temp:							
10000.0 megohm-microfarads							
Dissipation Factor At Reference Tempurature In Percent:							
1.000							
Dielectric Material:							
Plastic polyethylene terephthalate							
Terminal Type And Quantity:							
2 uninsulated wire lead							
Shelf Life:							

N/a

NSN 5910-01-149-4245

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0