

View Online at <https://aerobasegroup.com/nsn/5910-01-149-5122>

Body Style:

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

Dummy Terminal Quantity:

111

Reliability Indicator:

Not established/not established/not established

Terminal Length:

20.0 millimeters 20.0 millimeters 20.0 millimeters

Body Diameter:

31.0 millimeters

Body Length:

53.0 millimeters

Center To Center Distance Between Terminals Parallel To Diameter:

Between 14.5 millimeters and 15.5 millimeters

Terminal Diameter:

1.2 millimeters

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Impedance At Minimum Operating Temperature In Ohms:

3.0

Electrical Polarization:

Polarized

End Application:

6625-01-086-2271 multimeter assembly

Capacitance Value Per Section:

0.010 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Temperature In Percent:

30.000

Dc Leakage At Reference Temp:

3.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0