NSN 5910-01-150-3495

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-150-3495

Body	Stv	٠ ما
DOUV	OLV.	ıe.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:

Not establishednot established

Terminal Length:

2.500 inches 2.500 inches

Body Diameter:

0.937 inches

Body Length:

2.343 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.300 inches

Terminal Diameter:

0.040 inches

Schematic Diagram Designator:

Two common terminals for each electrode

Impedance At Minimum Operating Tempurature In Ohms:

0.39

Electrical Polarization:

Polarized

Capacitance Value Per Section:

100.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

424.3 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-10.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

1 20

Dc Leakage At Reference Temp:

70.700 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

NSN 5910-01-150-3495

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal '	Type	And	Quantity:
------------	------	-----	-----------

4 u-shaped tab

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0