

View Online at <https://aerobasegroup.com/nsn/5910-01-150-6359>

**Body Style:**

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

**Reliability Indicator:**

Not established/not established/not established

**Terminal Length:**

0.250 inches 0.250 inches 0.250 inches

**Body Diameter:**

2.578 inches

**Body Length:**

5.250 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.250 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Impedance At Minimum Operating Temperature In Ohms:**

6.0

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

640.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

0.7 milliamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

250.0 dc single section

**Tolerance Range Per Section:**

-10.00/+75.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.50

**Dc Leakage At Reference Temp:**

6.000 milliamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0