## NSN 5910-01-150-8535

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-150-8535

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.495 inches
Body Width:
0.495 inches
Body Height:
0.145 inches
Center To Center Distance Between Terminals Parallel To Length:
0.400 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
3.300 microfarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-15.0/+15.0 with rated voltage applied single section
-15.0/+15.0 with rated voltage applied single section
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section:
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 2.5000
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:  2.5000  Terminal Surface Treatment:
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 2.5000  Terminal Surface Treatment: Solder
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 2.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity:
-15.0/+15.0 with rated voltage applied single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 125.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  50.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Plastic  Insulation Resistance At Reference Temp: 100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 2.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead

--

## NSN 5910-01-150-8535

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0