NSN 5910-01-152-6983

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-152-6983

Body Style:		
W/o mtg facilities, axial terminals		
Reliability Indicator:		
Established		
Reliability Failure Rate Level In Percent:		
0.1000		
Terminal Length:		
1.625 inches		
Body Diameter:		
1.047 inches		
Body Length:		
2.437 inches		
Terminal Diameter:		
0.032 inches		
Schematic Diagram Designator:		
No common or grounded electrode (s)		
Insulation Resistance At Maximum Operating Temp:		
25000.0 megohms		
Capacitance Value Per Section:		
10.000 microfarads single section		
Nonderated Operating Temp:		
Between -65.0 degrees celsius and 85.0 degrees celsius		
Nonderated Continuous Voltage Rating And Type Per Section:		
30.0 dc single section		
Tolerance Range Per Section:		
-2.00/+2.00 percent single section		
Case Material:		
Metal		
Insulation Resistance At Reference Temp:		
100000.0 megohms		
Dissipation Factor At Reference Tempurature In Percent:		
0.6000		
Terminal Surface Treatment:		
Solder		
Case Insulation Material:		
Plastic		
Test Data Document:		
81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification		
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain		
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).		
Terminal Type And Quantity:		
2 uninsulated wire lead		

81349-mil-c-19978/13 government specification

Specification Data:

NSN 5910-01-152-6983

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Sh	elf	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0