## NSN 5910-01-153-0234

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-153-0234

Body Style:
W/thd mtg bushing, terminals on opposite ends
Reliability Indicator:
Not established
Width Across Flats:
0.187 inches
Terminal Length:
0.375 inches
Body Length:
0.349 inches
Schematic Diagram Designator:
Feedthrough
End Application:
Wasp class lhd; aircraft, hornet f/a-18; aircraft, prowler ea-6b; calibration standards equipment; support equipment, b-52 aircraft;
support equipment, f-15 aircraft; general purpose electronic test equipment gpete
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
1 threaded bushing
Capacitance Value Per Section:
1000.000 picofarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-7.5/+7.5 with rated voltage applied single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.164 inches
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Criticality Code Justification:
Feat
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Terminal Surface Treatment:
Solder
Special Features:
Weapon system essential

Shelf Life:

**Terminal Type And Quantity:** 

2 uninsulated wire lead

N/a

## NSN 5910-01-153-0234

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0