NSN 5910-01-155-1317

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-155-1317 **Body Style:** Piston **Overall Length:** 0.460 inches **Body Length:** 0.340 inches **Overall Diameter:** 0.310 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -150.0/+150.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.220 inches **Quality Factor At 25 Deg Celsius:** 800.0 **Terminal Width:** 0.031 inches **Terminal Thickness:** 0.015 inches **Inclosure Type: Encased Terminal Location:** Circumference on adjustment control end bent backward **Adjustment Device Torque:** Between 0.500 inch-ounces and 5.000 inch-ounces **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +1.5/+10.0 single section **Nonderated Voltage Rating And Type:** 250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a

Unit Of Measure:

NSN 5910-01-155-1317

Glass Dielectric Variable Capacitor - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A096a0