

View Online at https://aerobasegroup.com/nsn/5910-01-155-3717

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.0000

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.150 inches

**Body Length:** 

0.400 inches

**Terminal Diameter:** 

0.020 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

70000.0 megohms

### **Capacitance Value Per Section:**

0.047 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

## **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

#### **Case Material:**

Plastic

Insulation Resistance At Reference Temp:

500000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

0.3000

## **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-55514/4 government specification

Shelf Life:



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0