NSN 5910-01-155-7672

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-155-7672 **Body Style: Dual inline Reliability Indicator:** Not established **Terminal Length:** Between 0.120 inches and 0.176 inches **Body Length:** Between 0.087 inches and 0.098 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.135 inches **Center To Center Distance Between Terminals Parallel To Width:** Between 0.300 inches and 0.400 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** 5840-01-086-4730, processor, signal **Capacitance Value Per Section:** 0.0022 microfarads single section **Voltage Tempurature Limits Per Section In Percent Capacitance Change:** -15.0/+15.0 without voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 1000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 2.5000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 printed circuit Shelf Life: N/a

--

Unit Of Measure:

NSN 5910-01-155-7672

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0