

View Online at <https://aerobasegroup.com/nsn/5910-01-156-7072>

Body Style:

Dual inline

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.0100

Terminal Length:

0.148 inches

Body Length:

0.092 inches

Body Width:

0.260 inches

Body Height:

0.128 inches

Center To Center Distance Between Terminals Parallel To Width:

0.325 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

5810-01-111-4080, special test set k

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

2200.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

0.1500

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 printed circuit

Specification Data:

81349-mil-c-39014/22 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0