

View Online at <https://aerobasegroup.com/nsn/5910-01-157-5647>

Body Style:

W/o mtg facilities, axial terminals/w/o mtg facilities, axial terminals

Reliability Indicator:

Not established/not established

Terminal Length:

2.500 inches/2.500 inches

Body Diameter:

0.885 inches

Body Length:

1.843 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.300 inches

Terminal Diameter:

0.040 inches

Schematic Diagram Designator:

Two common terminals for each electrode

Impedance At Minimum Operating Temperature In Ohms:

0.460

Electrical Polarization:

Polarized

Capacitance Value Per Section:

85.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

390.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

1.530

Dc Leakage At Reference Temp:

65.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0