## NSN 5910-01-157-6652

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-157-6652 **Thread Class:** 2a **Body Style:** Piston **Terminal Length:** 1.131 inches **Bushing Diameter:** 0.288 inches **Bushing Length:** 0.218 inches **Body Length:** 0.910 inches **Overall Diameter:** 0.288 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -20.0/+20.0 single section **Quality Factor At 25 Deg Celsius:** 2000.0 **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Tuning Characteristic:** Straight line capacity single section **Adjustment Device Torque:** Between 1.000 inch-ounces and 5.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 12 **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.234 inches

**Capacitance Range In Picofarads:** 

+1.0/+30.0 single section

## NSN 5910-01-157-6652

Air Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Rating And Type:
250.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
1 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A096a0