

View Online at <https://aerobasegroup.com/nsn/5910-01-158-9045>

**Body Style:**

W/o mtg facilities terminal (s) on one surface/w/o mtg facilities terminal(s) on one surface

**Reliability Indicator:**

Not established/not established

**Terminal Length:**

Between 1.500 inches and 1.500 inches and 1.750 inches 1.750 inches

**Body Length:**

0.230 inches

**Body Width:**

0.310 inches

**Body Height:**

0.130 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.175 inches and 0.225 inches

**Terminal Diameter:**

0.015 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Electrical Polarization:**

Polarized

**End Application:**

5855-01-047-3231 basic sight assembly

**Capacitance Value Per Section:**

22.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

45.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

15.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.0000

**Dc Leakage At Reference Temp:**

3.000 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0