NSN 5910-01-158-9048



Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2	Grou
View Online at https://aerobasegroup.com/nsn/5910-01-158-9048	
Body Style:	
W/o mtg facilities, axial terminals	
Reliability Indicator:	
Established	
Reliability Failure Rate Level In Percent:	
0.0010	
Terminal Length:	
1.625 inches	
Body Diameter:	
0.530 inches	
Body Length:	
1.375 inches	
Terminal Diameter:	
0.032 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Features Provided:	
Hermetically sealed case	
Insulation Resistance At Maximum Operating Temp:	

10000.0 megohms

Capacitance Value Per Section:

3.300 microfarads single section

Nonderated Operating Temp:

Between -65.0 degrees celsius and 100.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-1.00/+1.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.1500

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Special Features:

length 1.375 inches; height 0.530 inches; width 0.530 inches

Test Data Document:

81349-mil-c-83421 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-01-158-9048

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:
2 uninsulated wire lead
Specification Data:
81349-mil-c-83421/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0