NSN 5910-01-159-2342

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-159-2342

| Body Style: |
|---|
| W/o mtg facilities, terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.560 inches |
| Body Length: |
| 1.910 inches |
| Body Width: |
| 2.910 inches |
| Body Height: |
| Between 3.820 inches and 4.000 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.810 inches |
| Schematic Diagram Designator: |
| No common or grounded electrodes, w/separate case terminal |
| Section Quantity: |
| 2 |
| Capacitance Value Per Section: |
| 20.000 microfarads 1st section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 75.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 330.0 ac-rms all sections |
| Tolerance Range Per Section: |
| -6.00/+6.00 percent all sections |
| Case Material: |
| Metal |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.100 |
| Terminal Type And Quantity: |
| 3 quick disconnect, male, double blade |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Δ010b0 |