## NSN 5910-01-160-2024

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-160-2024

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
2.000 inches
Body Length:
0.400 inches
Body Width:
0.090 inches
Body Height:
0.180 inches
Terminal Diameter:
0.016 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
10000.0 megohms
Capacitance Value Per Section:
8200.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
-5.00/+5.00 percent single section  Case Material:
Case Material:
Case Material: Plastic
Case Material: Plastic Insulation Resistance At Reference Temp:
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent:
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.5000
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment:
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder
Case Material:  Plastic  Insulation Resistance At Reference Temp:  100000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:  0.5000  Terminal Surface Treatment:  Solder  Terminal Type And Quantity:
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

No

## NSN 5910-01-160-2024

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0