## NSN 5910-01-160-8770

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-160-8770

Body Style:					
W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals					
Reliability Indicator:					
Not establishednot established					
Terminal Length:					
1.380 inches 1.380 inches 1.380 inches					
Body Diameter:					
0.630 inches					
Body Length:					
1.240 inches					
Terminal Diameter:					
0.032 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Impedance At Minimum Operating Tempurature In Ohms:					
2.0					
Electrical Polarization:					
Polarized					
Capacitance Value Per Section:					
680.000 microfarads single section					
Nonderated Operating Temp:					
Between -40.0 degrees celsius and 85.0 degrees celsius					
Nonderated Continuous Voltage Rating And Type Per Section:					
50.0 dc single section					
Tolerance Range Per Section:					
-20.00/+20.00 percent single section					
Case Material:					
Metal					
Capacitive Electrode Material:					
Aluminum					
Dissipation Factor At Reference Tempurature In Percent:					
12.0000					
Dc Leakage At Reference Temp:					
3.000 microamperes					
Terminal Surface Treatment:					
Solder					
Case Insulation Material:					
Plastic					
Terminal Type And Quantity:					
2 uninsulated wire lead					
Shalf Life:					

N/a

## NSN 5910-01-160-8770

Electrolytic Fixed Capacitor - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A010b0