

View Online at <https://aerobasegroup.com/nsn/5910-01-161-3255>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

0.077 inches

Body Diameter:

2.500 inches

Body Length:

4.048 inches

Center To Center Distance Between Terminals Parallel To Diameter:

1.125 inches

Terminal Diameter:

0.190 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Nimitz class cvn; close in weapon system (ciws-phalanx); virginia class cgn (41); oliver perry class ffg; ticonderoga class cg (47); kidd class ddg; arleigh burke class ddg; spruance class dd (963); forrestal class cv

Capacitance Value Per Section:

26000.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.069

Dc Leakage At Reference Temp:

6.000 milliamperes

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0