## NSN 5910-01-162-0747

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-162-0747

Rody	Style:
Douv	Style.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

## **Reliability Indicator:**

Not establishednot established

## **Terminal Length:**

1.181 inches 1.181 inches 1.181 inches

**Body Diameter:** 

0.492 inches

**Body Length:** 

0.984 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.197 inches

**Terminal Diameter:** 

0.032 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case, w/gnd terminal

**Anode Type:** 

Plain foil

**Electrical Polarization:** 

Polarized

**End Application:** 

4920-01-105-6373 test set altimeter

**Capacitance Value Per Section:** 

330.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

63.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

10.000

Dc Leakage At Reference Temp:

407.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

## NSN 5910-01-162-0747

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type A	nd Quantity:
-----------------	--------------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0