## NSN 5910-01-162-7261



Plastic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-162-7261 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 2.0000 **Terminal Length:** 1.625 inches **Body Diameter:** 0.400 inches **Body Length:** 0.874 inches **Terminal Diameter:** Between 0.031 inches and 0.036 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 0.027 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.1500 **Terminal Surface Treatment:** Solder **Case Insulation Material:** 

**Dielectric Material:** Plastic polycarbonate **Plastic Terminal Type And Quantity:** 2 uninsulated wire lead

## NSN 5910-01-162-7261

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Sneit	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0