## NSN 5910-01-162-7263



Ceramic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-162-7263 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.300 inches **Body Width:** 0.300 inches **Body Height:** 0.100 inches Center To Center Distance Between Terminals Parallel To Length: 0.200 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** Receiving set, countermeasures an/wlr-8 **Capacitance Value Per Section:** 2200.000 picofarads single section **Voltage Tempurature Limits Per Section In Percent Capacitance Change:** -30.0/+30.0 with rated voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 picofarads single section Case Material: Ceramic **Dissipation Factor At Reference Tempurature In Percent:** 0.1500 **Terminal Surface Treatment:** Solder

## **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5910-01-162-7263

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0