## NSN 5910-01-163-0422

Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-163-0422   |
|---|
| Body Style:   |
| W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end |
| Reliability Indicator:  |
| Not establishednot established  |
| Terminal Length:  |
| 1.370 inches 1.370 inches 1.370 inches  |
| Body Diameter:  |
| 0.216 inches  |
| Body Length:  |
| 0.472 inches  |
| Center To Center Distance Between Terminals Parallel To Diameter:   |
| 0.078 inches  |
| Terminal Diameter:  |
| 0.020 inches  |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)   |
| Electrical Polarization:  |
| Polarized   |
| Capacitance Value Per Section:  |
| 0.470 microfarads single section  |
| Nonderated Operating Temp:  |
| Between -40.0 degrees celsius and 85.0 degrees celsius  |
| Nonderated Continuous Voltage Rating And Type Per Section:  |
| 50.0 dc single section  |
| Tolerance Range Per Section:  |
| -10.00/+75.00 percent single section  |
| Case Material:  |
| Metal   |
| Capacitive Electrode Material:  |
| Aluminum  |
| Dc Leakage At Reference Temp:   |
| 4.000 microamperes  |
| Terminal Surface Treatment:   |
| Solder  |
| Case Insulation Material:   |
| Plastic   |
| Terminal Type And Quantity:   |

Shelf Life:

Unit Of Measure:

2 uninsulated wire lead

--

N/a

## NSN 5910-01-163-0422

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0