NSN 5910-01-163-9080

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-163-9080 |
|---|
| Body Style: |
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.276 inches |
| Body Length: |
| 0.400 inches |
| Body Width: |
| 0.460 inches |
| Body Height: |
| 0.150 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| 0.200 inches |
| Terminal Diameter: |
| 0.020 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.100 microfarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -15.0/+15.0 without voltage applied single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 200.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 1000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 2.5000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |

Unit Of Measure:

NSN 5910-01-163-9080

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0