NSN 5910-01-163-9082

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-163-9082

Body Style:

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not establishednot established

Terminal Length:

Between 1.000 inches and 1.000 inches and 1.750 inches 1.750 inches

Body Diameter:

1.010 inches

Body Length:

1.640 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.400 inches

Terminal Diameter:

0.040 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Impedance At Minimum Operating Tempurature In Ohms:

0.03

Electrical Polarization:

Polarized

End Application:

1270-01-132-2437 antenna radar

Capacitance Value Per Section:

2200.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

525.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Tempurature In Percent:

12.0000

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.051

Dc Leakage At Reference Temp:

105.000 microamperes

NSN 5910-01-163-9082 Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0