

View Online at <https://aerobasegroup.com/nsn/5910-01-164-5583>

**Body Style:**

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

**Dummy Terminal Quantity:**

111

**Reliability Indicator:**

Not established/not established/not established

**Terminal Length:**

Between 0.235 inches and 0.235 inches and 0.235 inches and 0.265 inches 0.265 inches 0.265 inches

**Body Diameter:**

1.010 inches

**Body Length:**

Between 1.078 inches and 1.202 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 0.385 inches and 0.415 inches

**Terminal Diameter:**

0.040 inches

**Schematic Diagram Designator:**

Two terminals common to one electrode

**Impedance At Minimum Operating Temperature In Ohms:**

0.06

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

1000.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

94.8 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

15.0 dc single section

**Tolerance Range Per Section:**

-10.00/+100.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.17

**Dc Leakage At Reference Temp:**

15.800 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

3 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0