## NSN 5910-01-164-5584

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-164-5584

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

## **Reliability Indicator:**

Not establishednot established

**Terminal Length:** 

0.980 inches 0.980 inches 0.980 inches

**Body Diameter:** 

0.413 inches

**Body Length:** 

0.866 inches

**Center To Center Distance Between Terminals Parallel To Diameter:** 

0.197 inches

**Terminal Diameter:** 

0.024 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Impedance At Minimum Operating Tempurature In Ohms:** 

4.0

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

100.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

63.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

0.1000

Dc Leakage At Reference Temp:

4.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-164-5584

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0