NSN 5910-01-165-8443

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-165-8443

Body Style:
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end
Reliability Indicator:
Not establishednot established
Terminal Length:
0.984 inches 0.984 inches 0.984 inches
Body Diameter:
0.414 inches
Body Length:
0.551 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.200 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Etched foil
Impedance At Minimum Operating Tempurature In Ohms:
3.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
47.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 105.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dc Leakage At Reference Temp:
0.005 microamperes

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

Terminal Surface Treatment:

2 uninsulated wire lead

NSN 5910-01-165-8443

Electrolytic Fixed Capacitor - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0