## NSN 5910-01-166-2716

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-166-2716

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not establishednot established

## **Terminal Length:**

Between 1.500 inches and 1.500 inches and 1.500 inches and 2.000 inches 2.000 inches 2.000 inches

**Body Diameter:** 

0.385 inches

**Body Length:** 

1.286 inches

**Terminal Diameter:** 

0.032 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Electrical Polarization:** 

Polarized

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

200.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 105.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+75.00 percent single section

Case Material:

Metal

**Capacitive Electrode Material:** 

Aluminum

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

0.31

Dc Leakage At Reference Temp:

1.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-166-2716

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0