NSN 5910-01-166-2835

Body Style:Dual inline

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-166-2835

Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.0100
Terminal Length:
0.148 inches
Body Length:
0.092 inches
Body Width:
0.260 inches
Body Height:
0.155 inches
Center To Center Distance Between Terminals Parallel To Width:
0.325 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
5840-01-084-5293 antenna-transceiver group
Insulation Resistance At Maximum Operating Temp:
10000.0 megohms
Capacitance Value Per Section:
0.100 microfarads single section
Voltage Tempurature Limits Per Section In Percent Capacitance Change:
-25.0/+15.0 with rated voltage applied single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
2.5000
Terminal Surface Treatment:
Solder
Test Data Document:

81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5910-01-166-2835

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity:
2 printed circuit
Specification Data:
81349-mil-c-39014/22 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0