

View Online at <https://aerobasegroup.com/nsn/5910-01-167-3018>

Thread Class:

2a

Body Style:

Piston

Overall Length:

0.578 inches

Terminal Length:

0.109 inches

Bushing Diameter:

0.234 inches

Bushing Length:

0.188 inches

Body Length:

0.390 inches

Overall Diameter:

0.281 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-75.0/+75.0 single section

Terminal Diameter:

0.093 inches

Quality Factor At 25 Deg Celsius:

2000.0

Mounting Facility Screw Thread Series Designator:

Uns

Inclosure Type:

Encased

Adjustment Device Rotation:

7.0 turns clockwise

Adjustment Device Torque:

Between 0.500 inch-ounces and 5.000 inch-ounces

Bushing Shape:

Round

Insulation Dc Resistance At 25 Deg Celsius:

100000.0 megohms

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

64

Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.234 inches

Capacitance Range In Picofarads:

+1.0/+10.0 single section

Nonderated Voltage Rating And Type:

200.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Material:

Aluminum insulation supporting

Terminal Type And Quantity:

1 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0