## NSN 5910-01-167-3018

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-167-3018 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.578 inches **Terminal Length:** 0.109 inches **Bushing Diameter:** 0.234 inches **Bushing Length:** 0.188 inches **Body Length:** 0.390 inches **Overall Diameter:** 0.281 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -75.0/+75.0 single section **Terminal Diameter:** 0.093 inches **Quality Factor At 25 Deg Celsius:** 2000.0 **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Adjustment Device Rotation:** 7.0 turns clockwise **Adjustment Device Torque:** Between 0.500 inch-ounces and 5.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 100000.0 megohms **Mounting Facility Type And Quantity:** 1 threaded bushing

Thready Qty Per Inch (tpi):

**Nonderated Operating Temp:** 

Between -65.0 degrees celsius and 125.0 degrees celsius

## NSN 5910-01-167-3018

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Thread Size:
0.234 inches
Capacitance Range In Picofarads:
+1.0/+10.0 single section
Nonderated Voltage Rating And Type:
200.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Material:
Aluminum insulation supporting
Terminal Type And Quantity:
1 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A096a0