NSN 5910-01-167-3301

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-167-3301 **Body Style:** W/o mtg facilities, terminal (s) on one surface **Reliability Indicator:** Not established **Body Length:** 8.000 inches **Body Width:** 4.000 inches **Body Height:** 12.000 inches **Center To Center Distance Between Terminals Parallel To Length:** 4.500 inches **Terminal Diameter:** 0.500 inches **Terminal Height From Body:** 2.813 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **End Application:** Transmitting set, radio an/frt-64 **Insulation Resistance At Maximum Operating Temp:** 1500.0 megohms **Capacitance Value Per Section:** 3.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 15000.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 50000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.5000 **Dielectric Material:** Paper and plastic

2 standoff, solder stud

Terminal Type And Quantity:

NSN 5910-01-167-3301

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A010b0