

View Online at <https://aerobasegroup.com/nsn/5910-01-167-3306>

**Body Style:**

Chip type

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

1.0000

**Terminal Length:**

0.015 inches

**Body Length:**

0.110 inches

**Body Width:**

0.110 inches

**Body Height:**

Between 0.030 inches and 0.102 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.095 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:**

100000.0 megohms

**Capacitance Value Per Section:**

240.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

90.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc single section

**Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Tolerance Range Per Section:**

-2.00/+2.00 percent single section

**Case Material:**

Ceramic or glass

**Insulation Resistance At Reference Temp:**

1000000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

0.0500

**Quality Factor At Reference Temp:**

1.8000

**Precious Material And Location:**

Terminal surfaces palladium and terminal surfaces silver

**Test Data Document:**

81349-mil-c-55681 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 bonding pad

**Specification Data:**

81349-mil-c-55681/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0