## NSN 5910-01-167-5936

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-167-5936 **Body Style:** W/thd bushing mtg, terminals on opposite ends **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.400 inches **Body Length:** 1.000 inches **Continuous Current Rating In Amps:** 10.0 **Terminal Diameter:** 0.051 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Mounting Facility Screw Thread Series Designator:** Unf **Mounting Facility Type And Quantity:** 1 threaded bushing **Capacitance Value Per Section:** 100.000 nanofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.312 inches Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Thread Tolerance Class:** 2a external **Case Material:** Metal **Insulation Resistance At Reference Temp:** 100000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.3000 **Terminal Type And Quantity:** 2 tab, solder lug

Shelf Life:

N/a

## NSN 5910-01-167-5936

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0