Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-168-5084

# **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Reliability Failure Rate Level In Percent:** 

1.0000

### **Terminal Length:**

1.625 inches

### **Body Diameter:**

0.562 inches

**Body Length:** 

1.125 inches

**Terminal Diameter:** 

0.025 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

# **Capacitance Value Per Section:**

1.000 microfarads single section

## Nonderated Operating Temp:

Between -65.0 degrees celsius and 100.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

## Case Insulation Material:

Plastic

## **Test Data Document:**

81349-mil-c-83421 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-83421/1 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No



**Fiig:** A010b0