NSN 5910-01-168-5868

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-168-5868 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.460 inches **Body Length:** 1.438 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **End Application:** 1270-01-132-2680 transmitter, rad **Insulation Resistance At Maximum Operating Temp:** 22.7 megohms **Capacitance Value Per Section:** 0.033 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 170.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.0200 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polytetrafluoroethylene **Case Insulation Material:**

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-168-5868

Plastic Dielectric Fixed Capacitor - Page 2 of 2



N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0