

View Online at <https://aerobasegroup.com/nsn/5910-01-168-6086>

**Body Style:**

Chip typechip typechip type

**Reliability Indicator:**

Not establishednot establishednot established

**Terminal Length:**

Between 0.025 inches and 0.025 inches and 0.025 inches and 0.045 inches 0.045 inches 0.045 inches

**Body Length:**

Between 0.185 inches and 0.195 inches

**Body Width:**

Between 0.070 inches and 0.090 inches

**Body Height:**

Between 0.045 inches and 0.065 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Impedance At Minimum Operating Temperature In Ohms:**

3.0

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

2.200 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

20.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.000

**Dc Leakage At Reference Temp:**

1.000 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 bonding pad

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0