NSN 5910-01-169-2076

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-169-2076 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Terminal Length:** Between 1.250 inches and 1.750 inches **Body Diameter:** 0.312 inches **Body Length:** Between 0.907 inches and 1.031 inches **Terminal Diameter:** Between 0.023 inches and 0.027 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Impedance At Minimum Operating Tempurature In Ohms:** 55.0 **Electrical Polarization:** Polarized **End Application:** Lcm-30 **Capacitance Value Per Section:** 60.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 2.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 15.0 dc single section **Tolerance Range Per Section:** -15.00/+75.00 microfarads single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5910-01-169-2076

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0