## NSN 5910-01-169-7935

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-169-7935 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.562 inches **Body Length:** 1.375 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **End Application:** 1420-01-119-4989, guidance section **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 5000.0 megohm-microfarads **Capacitance Value Per Section:** 10.000 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 100.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 300000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 2.0000 **Terminal Surface Treatment:** Solder **Case Insulation Material:** Plastic **Terminal Type And Quantity:** 2 uninsulated wire lead

N/a

Shelf Life:

## NSN 5910-01-169-7935

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0