NSN 5910-01-169-7937

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-169-7937 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.400 inches **Body Length:** 1.375 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 3000.0 megohm-microfarads **Capacitance Value Per Section:** 6.800 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 100.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 100000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.1500 **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

--

Unit Of Measure:

NSN 5910-01-169-7937

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| _ | | •• | • - | | | | |
|---|----|----|-----|-----|-------------|-----|----|
| 1 | em | | ゖっ | riz | 2 †1 | n | |
| _ | | | ıιa | 114 | au | VII | ١. |

No

Fiig:

A010b0