

View Online at <https://aerobasegroup.com/nsn/5910-01-170-0430>

**Body Style:**

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

**Reliability Indicator:**

Not established/not established/not established

**Terminal Length:**

2.000 inches 2.000 inches 2.000 inches

**Body Diameter:**

0.844 inches

**Body Length:**

1.400 inches

**Center To Center Distance Between Terminals Parallel To Diameter:**

Between 0.235 inches and 0.315 inches

**Terminal Diameter:**

Between 0.034 inches and 0.043 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Electrical Polarization:**

Polarized

**End Application:**

5815-01-108-5633 teleprinter

**Capacitance Value Per Section:**

470.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 105.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

25.0 dc single section

**Tolerance Range Per Section:**

-10.00/+100.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

10.0000

**Equivalent Series Resistance At Reference Temperature In Ohms:**

0.10

**Dc Leakage At Reference Temp:**

250.000 milliamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0