NSN 5910-01-170-1530

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-170-1530

Body Style:
W/thd mtg stud, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
0.406 inches
Body Diameter:
1.125 inches
Body Length:
1.705 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
30.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
360.0 dc single section
Tolerance Range Per Section:
20.00/+20.00 percent single section
Case Material:
Ceramic
Capacitive Electrode Material:
Tantalum
Dc Leakage At Reference Temp:
19.000 microamperes
Test Data Document:
31349-mil-c-3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
1 tab, solder lug
Specification Data:
31349-mil-c-3965/19 government specification
Shelf Life:
N/a

No

Unit Of Measure:

Demilitarization:

NSN 5910-01-170-1530

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0