NSN 5910-01-170-1732



Plastic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-170-1732 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 25.4 millimeters **Body Diameter:** 8.6 millimeters **Body Length:** 12.0 millimeters **Terminal Diameter:** 0.8 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 390.000 picofarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 70.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 160.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -80.0/+80.0 single section **Tolerance Range Per Section:** -2.00/+2.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polystyrene **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

Unit Of Measure:

N/a

NSN 5910-01-170-1732

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0