NSN 5910-01-171-5685

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-171-5685

Body Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Dummy Terminal Quantity:

11

Reliability Indicator:

Not establishednot established

Terminal Length:

1.000 inches 1.000 inches

Body Diameter:

0.885 inches

Body Length:

2.140 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.030 inches

Terminal Diameter:

0.040 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Impedance At Minimum Operating Tempurature In Ohms:

0.2

Electrical Polarization:

Polarized

Capacitance Value Per Section:

2200.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

590.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.044

Dc Leakage At Reference Temp:

118.000 microamperes

NSN 5910-01-171-5685

Electrolytic Fixed Capacitor - Page 2 of 2

AeroBase Group

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0